

We are Essity - formerly BSN medical

ABN 84 095 746 204 BSN medical (Aust.) Pty Ltd

PO Box 337, Mount Waverley, Victoria, Australia 3149 Phone: 1300 276 633 Fax: +61 3 9574 5690 www.bsnmedical.com.au

SAFETY DATA SHEET (Australia & New Zealand)

Product Name: Fixapipe Bandage

SECTION 1. PRODUCT IDEN	TIFIER AND IDENTITY FOR THE CHEMICAL
Product Name/s:	FIXAPIPE BANDAGE
Product Material Name:	Not applicable
Recommended Use:	Component of FIXAPIPE pipe repair kit
SECTION 1A. SUPPLIER IN AL	ISTRALIA
Supplier Name:	BSN medical Australia Pty Ltd
Address:	Level 6, 211 Wellington Road Mulgrave 3170
Telephone:	1300 276 633
Emergency Telephone:	000
SECTION 1A. SUPPLIER IN NE	W ZEALAND
Supplier Name:	BSN medical Limited
Address:	103 Carlton Gore Road Newmarket Auckland 1023
Telephone:	0508 276 111
Emergency Telephone:	111



Product Name: FIXAPIPE BANDAGE

SECTION 2. HAZARD IDENTIFICATION				
Hazard Classification (including a statement of overall hazardous or dangerous nature):	HAZARDOUS SUBSTANCE. NON-DANGEROUS GOOD Contains a water-activated polyurethane resin with isocyanate end groups. Excessive exposure may cause irritation of the respiratory tract and lungs and pulmonary edema. May cause sensitisation by inhalation. May cause asthmatic signs and symptoms in hypersensitive people.			
Risk phrases:	Hazard Category	Harmful, Irrit	tant	
	R36/37/38 R42/43	_	eyes, respiratory sy sensitisation by inh	
Safety phrases:	\$23 \$24/25 \$36/37/39 \$26 \$46	Wear suitab eye/face pro In case of co with plenty of Poisons Info If swallowed	ct with skin and ey le protective clothi	ng, gloves and nse immediately et a doctor or vice immediately
SECTION 3. COMPOSITIO	N / INFORMA	ATION ON INC	GREDIENTS	
Pure Substances:				
Ingredient			CAS No.	Proportion (%)
Polyurethane prepolymer			Proprietary	51
Fibreglass			Not applicable	49
components:	The polyurethane prepolymer contains the following components:			
Diphenylmethane Diisocyanate (M.D.I.) Dimorpholinodiethylether (DMDEE Catalyst)		26447-40-5	6.9 - 7.5	
umorpnolinoalethylether (DN	IDEE Catalys	SL)	6425-39-4	< 0.14



Product Name: FIXAPIPE BANDAGE

SECTION 4. FIRST AID MEASURE	S	
Swallowed	Do not induce vomiting. Seek immediate medical attention.	
Eye	Rinse eye with water for 15 minutes, whilst lifting eyelid. Get medical attention if effects persist.	
Skin	Remove material from skin immediately by washing with soap and warm water. Seek medical attention if irritation persists.	
Inhaled	Move individual to fresh air. Give oxygen in the event of breathing difficulty. Apply artificial respiration if necessary. Seek medical attention if effects persist.	
First-Aid Facilities	Eye wash plus normal washroom facilities nearby.	
Advice to Doctor	Treat symptomatically. May cause respiratory sensitisation or asthma-like symptoms.	
SECTION 5. FIRE FIGHTING MEASURES		
Hazards from Combustion Products:	The product is not readily combustible but will burn under fire conditions and give off toxic fumes, mainly carbon monoxide and carbon dioxide and with a possibility of hydrogen cyanide and nitrogen oxides (dependent upon combustion conditions).	
Suitable Extinguishing Media:	Carbon dioxide, dry chemical, foam.	
Fire-fighting Procedures	Vapours are extremely irritating when inhaled. Fire fighters should wear protective clothing and self-contained breathing apparatus where decomposition fumes may be formed.	
SECTION 6. ACCIDENTIAL RELEA	SE MEASURES	
Spill / Leak Procedure	Ventilate the area thoroughly. Avoid skin contact. Wear impervious gloves (e.g. vinyl, latex, nitrile). Absorb the spilled compound in sawdust or other absorbent. Store temporarily in an open container. Absorbed material should be treated	



Product Name: FIXAPIPE BANDAGE

SECTION 7. HANDLING & STORAG	GE
Handling Advice	Wear gloves (provided with kit) when handling the product. Refer to instructions for use provided with the product.
Storage Advice	Store in a cool, dry, well-ventilated area away from strong oxidising agents. During storage, avoid contact with water, alcohols, strong bases, metal compounds or surface-active materials.
SECTION 8. EXPOSURE CONTRO	LS / PERSONAL PROTECTION
Exposure Standards	Isocyanates, all (as-NCO) (whilst the product is being cured, present as the polymer functional end groups). TWA 0.02 mg/m³ STEL 0.07 mg/ m³ Sensitiser In the event that the product requires removal using a
•	method which generates dust, please note that dusts containing cured isocyanate material may cause a reaction in sensitised individuals. For Nuisance Dust: TWA 10 mg/m³.
Engineering Controls	Provide good dilution ventilation when applying the bandage and activating the resin to set. In the event that the product must be removed, provide good dilution ventilation if using oscillating saws for product removal. The use of shears offers an effective method to remove the product without dust generation.
Personal Protection	Avoid prolonged skin contact. Impervious gloves (e.g. vinyl, latex, nitrile) should be worn to prevent skin contact with the unset resin. Eye protection (safety glasses or goggles) should be worn. Wear rubber or plastic apron to protect skin and clothing. Respiratory protection is not needed in normal applications. In case of need, use air supply mask or respirator with canister for organic vapours/ isocyanates.



Product Name: FIXAPIPE BANDAGE

SECTION 9. PHYSICAL & CHEMIC	CAL PROPERTIES
Appearance and Odour	Tacky resin-coated fibreglass, covered with felted polypropylene. Very slight odour. When activated by water, the polyurethane resin crosslinks to give a rigid material releasing carbon dioxide in small amounts. A small exotherm is evident when the recommended water temperatures are used.
Melting Point / Boiling Point	MP: Resin only <15°C BP: Resin decomposes at above 200°C
Vapour Pressure	0.0002 mmHg at 24°C
Vapour Density (Air=1)	Not available
Specific Gravity	S.G. of resin approx. 1.2
Flashpoint	Resin: flash point 218°C
Flammability Limits (FL) (%)	Lower FL: Not available Upper FL: Not available
Autoignition Temperature	Not available
Solubility in Water (g/L)	Insoluble. Resin reacts with water with evolution of CO_2 .
Percent volatile by volume	A small amount of carbon dioxide is released on cure.
SECTION 10. STABILITY & REACT	IVITY
Stability:	Stable at room temperature. Polymerisation may occur if product is heated for long periods.
Conditions to Avoid:	Heat sources and contact with water. Moisture contamination may form CO_2 gas pressure. Ensure water temperature is within recommended guidelines.
Incompatible Materials:	Avoid contact with water, alcohols, strong bases, metal compounds or surface-active materials.



Product Name: FIXAPIPE BANDAGE

Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide, nitrogen oxides, and the possibility of hydrogen cyanide. Moisture contamination may form CO ₂ gas pressure.
Hazardous Polymerisation:	May occur.
SECTION 11. TOXICOLOGY INFOR	MATION
Acute Effects	
Swallowed	Not a likely route of exposure. Single dose oral toxicity is considered to be extremely low. Small amounts swallowed incidental to normal handling operations are not likely to cause injury.
Eye	The unset resin system is potentially an irritant in direct contact with eyes. May cause very slight, temporary corneal damage. The resin vapour level at room temperature will not be sufficient to cause any health problems.
Skin	MDI LD ₅₀ for skin absorption in rabbits is >2000 mg/kg. DMDEE dermal toxicity in rabbits: LD ₅₀ 3058mg/kg. The unset resin system may cause skin sensitisation. It is potentially irritant in direct contact with skin. May stick to skin and cause irritation on removal. Prolonged skin contact or repeated exposure symptoms may include redness and a rash.



Product Name: FIXAPIPE BANDAGE

Inhaled	At temperatures higher than recommended (greater than 50°C), isocyanate-containing fumes may be generated. At room temperatures, vapours are minimal. May cause sensitisation by inhalation. Very low concentrations may cause asthmatic signs and symptoms in hypersensitive people. Short-term effects of exposures above the exposure standard may include breathing difficulties and sensitisation. In the event that the cured product requires removal, note the following: Removal using oscillating saws causes a potentially irritant dust, from the set isocyanate resin, to be released into the atmosphere. The fibreglass present in this dust may cause respiratory mechanical irritation.
Chronic Effects	Chronic or repeated exposure may cause skin irritation and sensitisation.
SECTION 12. ECOLOGICAL INFOR	MATION
Environmental Issues	The material is not considered to be dangerous to aquatic organisms.
Persistence & Degradability	In aqueous media, formation of insoluble and chemically inert polyureas will occur. No appreciable volatilisation from water to air is expected.
Mobility	Movement in the environment is expected to be limited due to the formation of insoluble polymers.
SECTION 13. DISPOSAL CONSIDE	RATIONS
Method of Disposal	In accordance with local waste regulations. Hardened material is not classified as a hazardous waste. Allow to cure and then send to standard industrial landfill. May be incinerated in an approved facility.
SECTION 14. TRANSPORT INFORM	MATION
Classification	Not classified as a Dangerous Good according to the Australian Code for Transport of Dangerous Goods by Road and Rail.



Product Name: FIXAPIPE BANDAGE

SDS Number: 003 Version of SDS: 2.0

UN No.	Not applicable
Class	Not applicable
Subsidiary Risk(s)	Not applicable
Packing Group	Not applicable
Hazchem Code	Not applicable
Shipping Name	Not applicable
Other	Not applicable
SECTION 15. REGULATORY INFO	RMATION
Poison Schedule:	Not a scheduled poison.
SECTION 16. OTHER INFORMATIO	ON CONTRACTOR OF THE PROPERTY
Date of Preparation or Review	The revision details are included at the end of this document.
Source(s) of Data:	Based on MSDS No. 192 (issued 16 April 2013).

This SDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company.

REVISION RECORD

Version	n Date	Description of Change	
1.0	3 Sept 2019	Updated to BSN medical template.	
2.0	23 July 2024	Document review period. Updated BSN NZ address. No change to the rest of the document contents.	



We are Essity - formerly BSN medical

ABN 84 095 746 204 BSN medical (Aust.) Pty Ltd

PO Box 337, Mount Waverley, Victoria, Australia 3149 Phone: 1300 276 633 Fax: +61 3 9574 5690 www.bsnmedical.com.au

SAFETY DATA SHEET (Australia & New Zealand)

Product Name: Fixapipe Steel Putty

SECTION 1. PRODUCT IDENT	TIFIER AND IDENTITY FOR THE CHEMICAL
Product Name/s:	FIXAPIPE STEEL PUTTY
Product Material Name:	Not applicable
Recommended Use:	Component of FIXAPIPE pipe repair kit
SECTION 1A. SUPPLIER IN AU	STRALIA
Supplier Name:	BSN medical Australia Pty Ltd
Address:	Level 6, 211 Wellington Road Mulgrave 3170
Telephone:	1300 276 633
Emergency Telephone:	000
SECTION 1A. SUPPLIER IN NE	W ZEALAND
Supplier Name:	BSN medical Limited
Address:	103 Carlton Gore Road Newmarket Auckland 1023
Telephone:	0508 276 111
Emergency Telephone:	111



SECTION 2. HAZARD IDEN	ITIFICATIO	ON		
Hazard Classification (including a statement of overall hazardous or dangerous nature):	Irritating	HAZARDOUS SUBSTANCE. NON-DANGEROUS GOOD Irritating to skin and eyes. May cause sensitisation by skin contact.		OUS GOOD
Risk phrases:	Hazard Category	Irritant y		
	R36/38 R43	Irritating to ey May cause se	res and skin. ensitization by skin o	contact.
Safety phrases:	\$24/25 \$37/39 \$26 \$28	Wear suitable In case of cor plenty of wate Information C After contact	with skin and eyes and eye/face gloves and eye/face and contact a documentre. with skin, wipe off, to the control of soap and contact and contact and contact and control of soap and con	ce protection. e immediately with stor or Poisons hen wash
SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS				
Pure Substances:				
Ingredient			Proportion (%)	CAS-No:
Diglycidyl Ether of Bisphenol	A		7% to 13%	25036-25-3
Diglycidyl Ether of Bisphenol	A		5% to 10%	25068-38-6
2,4,6-Tris(Dimethylamino)met	thyl phenol		0.5% to 1.5%	90-72-2
SECTION 4. FIRST AID ME	ASURES			
		omiting. Rinse mouth with water. istance if symptoms develop.		
Flush eyes thoroughly with water for several mi symptoms develop, consult a physician, prefer ophthalmologist.				
			ighly with plenty of p, seek medical ass	



Inhaled	N/A, vapours are unlikely.
First-Aid Facilities	Eye wash plus normal washroom facilities nearby.
Advice to Doctor	Consider additional thorough skin wash with mild, non-abrasive soap and plenty of warm water for at least fifteen minutes.
SECTION 5. FIRE FIGHTING MEASU	IRES
Suitable Extinguishing Media:	Foam, alcohol foam, CO2, dry chemical, water fog.
Hazards from Combustion Products:	Combustible. On burning, the product may emit toxic fumes including carbon monoxide, carbon dioxide and oxides and nitrogen and sulphur.
Fire-fighting Procedures	Respiratory equipment should be worn to avoid inhalation of concentrated vapours. Water should not be used, except as fog to keep nearby containers cool. Fire fighters and others who may be exposed to the products of combustion should be equipped with NISOH approved positive pressure self-contained breathing apparatus and full protective clothing.
SECTION 6. ACCIDENTIAL RELEAS	E MEASURES
SECTION 6. ACCIDENTIAL RELEAS Spill / Leak Procedure	E MEASURES Ventilate the area. Wear protective equipment to prevent skin and eye contact. Dispose of in normal manner in accordance with local regulations. Not a hazardous waste.
	Ventilate the area. Wear protective equipment to prevent skin and eye contact. Dispose of in normal manner in accordance with local regulations. Not a hazardous waste.
Spill / Leak Procedure	Ventilate the area. Wear protective equipment to prevent skin and eye contact. Dispose of in normal manner in accordance with local regulations. Not a hazardous waste.
Spill / Leak Procedure SECTION 7. HANDLING & STORAGE	Ventilate the area. Wear protective equipment to prevent skin and eye contact. Dispose of in normal manner in accordance with local regulations. Not a hazardous waste. No special precautions needed. Always wear gloves (provided with kit) when handling the product. Refer to instructions for use provided with the product. Keep out
Spill / Leak Procedure SECTION 7. HANDLING & STORAGI Handling Advice	Ventilate the area. Wear protective equipment to prevent skin and eye contact. Dispose of in normal manner in accordance with local regulations. Not a hazardous waste. No special precautions needed. Always wear gloves (provided with kit) when handling the product. Refer to instructions for use provided with the product. Keep out of reach of children. Store in a cool, dry, well-ventilated area, away from ignition sources.
Spill / Leak Procedure SECTION 7. HANDLING & STORAGI Handling Advice Storage Advice	Ventilate the area. Wear protective equipment to prevent skin and eye contact. Dispose of in normal manner in accordance with local regulations. Not a hazardous waste. No special precautions needed. Always wear gloves (provided with kit) when handling the product. Refer to instructions for use provided with the product. Keep out of reach of children. Store in a cool, dry, well-ventilated area, away from ignition sources.



Personal Protection	Wear appropriate impervious gloves. Wear safety glasses or goggles. Respiratory protection is not needed when used in a well-ventilated area.	
SECTION 9. PHYSICAL & CHEMICAL PROPERTIES		
Appearance and Odour	Putty. Mercaptan/sulphur odour	
Melting Point / Boiling Point	Not available	
Vapour Pressure	Not available	
Vapour Density (Air=1)	Not available	
Specific Gravity	S.G. approx. 2.2	
Flashpoint	> 60°C	
Flammability Limits (FL) (%)	Lower FL: Not available Upper FL: Not available	
Autoignition Temperature	Not available	
Solubility in Water (g/L)	Insoluble	
Percent volatile by volume	< 0.1%	
SECTION 10. STABILITY & REACTIVITY		
Stability:	Stable under normal conditions of use.	
Conditions to Avoid:	Avoid exposure to heat and sources of ignition.	
Incompatible Materials:	None known.	
Hazardous Decomposition Products:	Carbon dioxide, aldehydes, acids, oxides of nitrogen and sulphur.	
Hazardous Polymerisation:	Will not occur.	
SECTION 11. TOXICOLOGY INFORMATION		
Acute Effects		



Swallowed	May result in nausea, vomiting and irritation of the gastric tract.	
Eye	May cause moderate eye irritation.	
Skin	Has caused allergic skin reactions in humans. A single exposure is not likely to cause skin irritation. Prolonged and repeated contact may cause skin irritation with local redness.	
Inhaled	Vapours are unlikely due to physical properties of the product.	
Chronic Effects	No data available	
SECTION 12. ECOLOGICAL INFORMATION		
Environmental Issues	No data available. Avoid contamination of sewers and waterways.	
Persistence & Degradability	No data available	
Mobility	No data available	
SECTION 13. DISPOSAL CONSIDERATIONS		
Method of Disposal	In accordance with local waste regulations. May be sent to standard industrial landfill or incinerated in an approved facility Not classified as hazardous waste.	
SECTION 14. TRANSPORT INFORMATION		
Classification	Not classified as a Dangerous Good according to the Australian Code for Transport of Dangerous Goods by Road and Rail.	
UN No.	Not applicable	
Class	Not applicable	
Subsidiary Risk(s)	Not applicable	
Packing Group	Not applicable	



Product Name: FIXAPIPE STEEL PUTTY
SDS Number: 004 Version of SDS: 2.0

Hazchem Code	Not applicable	
Shipping Name	Not applicable	
Other	Not applicable	
SECTION 15. REGULATORY INFORMATION		
Poison Schedule:	Not a scheduled poison.	
SECTION 16. OTHER INFORMATION		
Date of Preparation or Review	The revision details are included at the end of this document.	
Source(s) of Data:	Based on MSDS No. 193 (issued 16 April 2013).	

This SDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company.

REVISION RECORD

Version	Date	Description of Change
1.0	3 Sept 2019	Updated to BSN medical template.
2.0	23 July 2024	Document review period. Updated BSN NZ address. No change to the rest of the document contents.