

MC3009 Heavy-Duty Wheel Chock

Product Images



Short Description

- Rated for vehicles with a gross operating weight of 111,130 kgs
- Maximum rated payload of 63,503 kgs
- Recommended tyre diameter 116.8 cm to 165.1 cm
- Barcode imprinted on the back of chock
- Approved and being used by Caterpillar and mines worldwide
- ANSI compliant color guidelines on proper chocking and wheel chock placement in English
- Meets MSHA specifications
- Resistant to oils, fuels, and solvents
- Recessed carrying handle on the backside of the chock
- Replaceable rubber anti-slip traction pads
- Mounting hole for ropes, chains or brackets
- Molded-in "How to Use" guidelines in English
- Safety yellow color

Description

The Checkers™ industrial wheel chocks, MC3009 for ground vehicles are manufactured with highly durable, lightweight high-density polyethylene (HDPE) and they feature a larger base that makes them ideal for use with heavy equipment. MC3009 wheel chocks are designed for mine support equipment such as lubrication trucks and heavy maintenance vehicles. Rated for tire sizes up to 165.1 cm diameter and gross vehicle operating weight up to 111,130 kg. A maximum rated payload of 63,503kgs.

Specifications

Model No	MC3009
UPC	812542020008
Color	Yellow
Quantity Included	1
Pallet Quantity	48
Max Operating Weight	111,130 kgs
Recommended Tire Diameter	116.8 cm to 165.1 cm
Length (cm)	38.1
Width (cm)	38.4
Height (cm)	28
Weight (kg)	6.6
Material of Construction	Polyurethane
Sold As	Single

Prop 65

⚠️WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.