

MC3010 Heavy-Duty Wheel Chock

Product Images



Short Description

- Recommended tyre diameter 165.1 cm to 266.7 cm
- Barcode imprinted on back of chock
- Rated for vehicles with a max gross operating weight of 249,476 kg
- Maximum rated payloads of 49,685 kgs

- ANSI compliant color guidelines on proper chocking and wheel chock placement in English
- Meets MSHA specifications
- Recessed carrying handle on the backside of the chock
- Replaceable rubber anti-slip traction pads
- Molded-in "How to Use" guidelines in English
- Approved and being used by Caterpillar and mines worldwide
- Resistant to oils, fuels, and solvents
- Mounting hole for ropes, chains or brackets
- Safety yellow color

Description


The Checkers™ heavy-duty MC3010 wheel chocks for ground vehicles are manufactured with highly durable, lightweight high-density polyethylene (HDPE) and they feature a larger base that makes them ideal for use with heavy equipment such as haul trucks, loaders, and cranes.

MC3010 wheel chocks are for mine haul trucks with tire sizes up to 266.7 cm in diameter and gross vehicle operating weight up to 249,476 kg. A maximum rated payload of 49,685 kgs.

Specifications

Model No	MC3010
UPC	812542020015
Color	Yellow
Quantity Included	1
Pallet Quantity	36
Max Operating Weight (kg)	249,476
Recommended Tire Diameter (cm)	165.1 cm to 266.7 cm
Length (cm)	45
Width (cm)	38.7
Height (cm)	25.4
Weight (kg)	8.62
Material of Construction	Polyurethane
Sold As	Single

Prop 65

 **WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.