

MC3012 Heavy-Duty Chock

Product Images



Short Description

- Rated for vehicles with a gross operating weight up to 387,821 kgs
- Maximum rated payloads of 231,332 kgs
- Resistant to oils, fuels, and solvents
- Approved and being used by Caterpillar and mines worldwide
- Recommended tyre diameter 241.3 cm to 360.7 cm
- Barcode imprinted on back of chock
- ANSI compliant color guidelines on proper chocking and wheel chock placement in English
- Meets MSHA specifications
- Molded-in "How to Use" guidelines in English
- Safety yellow color

- Recessed carrying handle on the backside of the chock
- Replaceable rubber anti-slip traction pads
- Mounting hole for ropes, chains or brackets

Description

The Checkers™ heavy-duty MC3012 wheel chocks for ground vehicles are manufactured with highly durable, lightweight high-density polyethylene (HDPE) and they feature a larger base that makes them ideal for use with heavy equipment such as haul trucks, loaders, and cranes. MC3012 wheel chocks are for mine haul trucks with tyre sizes up to 241.3 cm in diameter and gross vehicle operating weight up to 387,821 kgs. A maximum rated payload of 231,332kgs. This chock is designed for normal haul road grades.

Specifications

Model No	MC3012
UPC	812542020039
Color	Yellow
Quantity Included	1
Pallet Quantity	27
Max Operating Weight (kg)	387,821
Recommended Tire Diameter (cm)	241.3 to 360.7
Length (cm)	55.7
Width (cm)	37.9
Height (cm)	27
Weight (kg)	10.8
Material of Construction	Polyurethane
Sold As	Single

Prop 65



WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.